PROFESSIONAL LINE

*Protective Treatments*

# B1 700

## Solvent-based, fast-drying stain-resistant treatment for natural stone, terracotta, and agglomerates.

**B1 700** is a solvent-based, fast-drying, stain-resistant treatment, specifically developed to protect without changing the color of the surface on which it is applied. The product dries quickly providing high stain-resistant features to the material.

**B1 700** is highly recommended for those surfaces that are prone to color changes when protected such as limestones. **B1 700** can also be used as a stain-resistant treatment in combination with a water-repellent treatment.

**BENEFITS**

- ✓ UV resistant
- ✓ High stain-resistant properties
- ✓ It doesn't change the color of the material
- ✓ It won't yellow overtime

**USES**

This product can be used on both indoor and outdoor surfaces.
Suitable for use on Marble, Sandstone, Limestone, Granite, Slate, Basaltina, Quartzite, Porphyry, Travertine, Cotto, Terracotta, Marble-resin agglomerate, Marble-cement agglomerate, Quartz-resin agglomerate.

**COVERAGE**

32 fl oz can cover 107-160 ft²

**APPLICATION EQUIPMENT**

Brush, Lambswool applicator, Roller, Cloth

**APPLICATION STEPS**

***Surface preparation***

- Carefully clean the surface, making sure to remove any dust or dirt present.
- Never apply **B1 700** to wet or damp surfaces.
- Apply **B1 700** to surfaces with a temperature between +5 and +40°C
- Any surfaces in direct proximity not being treated must be protected.

***Application***

*Before applying the product is necessary to take a preliminary test on an unexposed area or unused piece of material to check the product's suitability.*

- On a clean and dry surface apply a thin and even layer of product using the preferred tool making sure to cover the whole surface.
- The product dries very quickly without leaving residues. If residues appear to be present, they can easily be removed using a clean and dry cloth. On particularly absorbing surfaces we recommend applying a second coat. It is crucial to wait at least 30 minutes between applications.

***Drying Time***

The product dries quickly, within 30 minutes of the application.

***Resume Surface Use***

Resume the use of the surface after 2-3 hours from the application

MADE IN ITALY 100%



FABER CHIMICA SRL
60044 FABRIANO (AN) ITALY - VIA G. CERESANI 10 - LOC. CAMPO D'OLMO
PI-CF / VAT NUMBER 0100744021 - P: +39 0732 62 71 78
INFO@FABERSURFACECARE.COM - FABERSURFACECARE.COM

**MAINTENANCE PRODUCTS**

- For the daily cleaning of a surface treated with **B1 700**, we recommend: **NEUGEL** or **ALGAFLOOR**
- For heavy-duty cleaning of a surface treated with **B1 700**, we recommend: **FABER 30** or **DETERFUG** according to the type of material

**INSTRUCTIONS AND GUIDELINES**

- Never apply the product to wet or damp surfaces.
- If the product is applied as a stain-proof treatment on a material that has already been primed with a high penetrating water-repellent sealer, wait for this to dry completely before applying **B1 700.**
- Do not apply the product to overly heated surfaces.
- Do not apply the product when there is an imminent risk of rain or frost, or in the presence of mist, fog, or high levels of humidity.
- Apply the product to surfaces with a temperature of between +41 and +95°F
- When applying to recently laid or grouted surfaces, wait for the adhesive or grout to cure completely.
- Before applying the product to the whole surface, it is advisable to test a small, unexposed area or unused piece to check its suitability for use.

**EQUIPMENT CLEANING**

At the end of the application, the equipment used can be washed using white spirit.

**PHYSICAL-TECHNICAL DATA**

| | |
|---|---|
| Formula | Liquid |
| Color | Clear |
| Odor | Solvent |
| Specific gravity a 20°C | 810 ± 10 g/l |
| Flash Point (ASTM D 56) | < 21°C |

**STORAGE**

Keep the container tightly closed and store in a cool, dry place.

**SHELF LIFE**

24 months in the original, sealed packaging, stored in a cool, dry place.

**PACKAGING**

32 fl oz bottles – 12 bottles per box
169 fl oz bottles – 4 bottles per box

**SAFETY**

When applying the product, always use suitable personal protective equipment and follow the product safety data sheet instructions with care.

**Revisione 4.0 – 17/02/2025**

**This technical data sheet supersedes all previous versions. Always refer to the latest version of the data sheet, available on www.fabersurfacecare.com site. Faber Chimica reserves the right to update and/or modify the data and information contained in the datasheet.**

*The information in this data sheet is based on our wide experience in technical and operational research. In any case, you should always make a preliminary test to verify the suitability of the product for the intended use and the type of material on which it will be applied. The information and the suggestions can't be construed as a commitment or result in our responsibility as the conditions and method of use of the product cannot be controlled by us. Therefore Faber Chimica Srl disclaims any liability concerning the use of such data and suggestions.*



FABER CHIMICA SRL
60044 FABRIANO (AN) ITALY - VIA G. CERESANI 10 - LOC. CAMPO D'OLMO
PI-CF / VAT NUMBER 0100744021 - P: +39 0732 62 71 78
INFO@FABERSURFACECARE.COM - FABERSURFACECARE.COM

MADE IN ITALY
100%