PROFESSIONAL LINE

*Protective Treatments*

# DPS

## High-penetrating water-repellent solvent-based treatment highly effective on stones affected by humidity-related issues

**DPS** is an innovative solvent-based treatment that provides excellent water-repellent features to the treated surface. It protects against water absorption and rising humidity. Differently from the traditional treatments, **DPS** can be used even on surfaces that are already affected by humidity-related issues, like salt, efflorescences, rust, and oxidations.

**BENEFITS**

- ✓ UV resistant
- ✓ High-penetrating
- ✓ It won't change the breathability of the stone
- ✓ Suitable for surfaces affected by humidity-related issues

**USES**

This product can be used on both indoor and outdoor surfaces.
Suitable for use on Marble, Sandstone, Limestone, Granite, Slate, Basaltina, Quartzite, Porphyry, Travertine, Cotto, Terracotta, Marble-resin agglomerate, Marble-cement agglomerate, Quartz-resin agglomerate.

**COVERAGE**

32 fl oz can cover 107-160 ft²

**APPLICATION EQUIPMENT**

Brush, Lambswool applicator, Roller, Cloth

**APPLICATION STEPS**

***Surface preparation***

- Carefully clean the surface, making sure to remove any dust or dirt present.
- Never apply **DPS** to wet or damp surfaces.
- Apply **DPS** to surfaces with a temperature between +40 and +100°F
- Any surfaces in direct proximity not being treated must be protected.

***Application***

*Before applying the product is necessary to take a preliminary test on an unexposed area or unused piece of material to check the product's suitability.*

- Apply an even, abundant coat of product to a clean, dry surface with the preferred tool, making sure to create an even layer to cover the whole surface being treated. In the case of very absorbent material is possible to apply a second coat of product, "wet on wet". In this case, apply the second coat "crossing" the application of the first coat.
- After the application of the last coat of product wait about 10-15 minutes for the product penetration and then, if present, remove the residues of product by using a clean cloth.
- The product usually does not create residues. When applied to a compact surface that is not very absorbent, it could leave slight residues on the surface that can be easily wiped off with a clean, dry cloth or by using a single disc machine equipped with a soft white pad.

MADE IN ITALY 100%



FABER CHIMICA SRL
60044 FABRIANO (AN) ITALY - VIA G. CERESANI 10 - LOC. CAMPO D'OLMO
PI-CF / VAT NUMBER 0100744021 - P: +39 0732 62 71 78
INFO@FABERSURFACECARE.COM - FABERSURFACECARE.COM

PROFESSIONAL LINE

**APPLICATION STEPS**

***Drying Time***
The product dries quickly, within 1 hour of the application.

***Resume Surface Use***
Resume the use of the surface after 4 hours from the application

**MAINTENANCE PRODUCTS**

- For the daily cleaning of a surface treated with **DPS**, we recommend: **NEUGEL** or **ALGAFLOOR**
- For heavy-duty cleaning of a surface treated with **DPS**, we recommend: **FABER 30 2.0** or **DETERFUG** according to the type of material

**INSTRUCTIONS AND GUIDELINES**

- Never apply the product to wet or damp surfaces.
- Do not apply the product to overly heated surfaces.
- Do not apply the product when there is an imminent risk of rain or frost or in the presence of mist, fog, or high levels of humidity.
- Apply the product to surfaces with a temperature of between +40 and +100°F
- When applying to recently laid or grouted surfaces, wait for the adhesive or grout to cure completely.
- Before applying the product to the whole surface, it is advisable to test a small, unexposed area or unused piece to check its suitability for use.

**EQUIPMENT CLEANING**

At the end of the application, the equipment used can be washed using white spirit.

**PHYSICAL-TECHNICAL DATA**

| | |
|---|---|
| Formula | Liquid |
| Color | Clear |
| Odor | Solvent |
| Specific gravity a 20°C | 0.836 g/cm³ at 20°C |
| Flash Point (ASTM D 56) | < 21°C |

**STORAGE**

Keep the container tightly closed and store in a cool, dry place.

**SHELF LIFE**

12 months in the original, sealed packaging, stored in a cool, dry place.

**PACKAGING**

32 fl oz bottles – 12 bottles per box
169 fl oz bottles – 4 bottles per box

**SAFETY**

When applying the product, always use suitable personal protective equipment and follow the product safety data sheet instructions with care.

**Rev. 2.0 – 17/02/2025**

**This technical data sheet supersedes all previous versions. Always refer to the latest version of the data sheet, available on www.fabersurfacecare.com site. Faber Chimica reserves the right to update and/or modify the data and information contained in the datasheet.**

*The information in this data sheet is based on our wide experience in technical and operational research. In any case, you should always make a preliminary test to verify the suitability of the product for the intended use and the type of material on which it will be applied. The information and the suggestions can't be construed as a commitment or result in our responsibility as the conditions and method of use of the product cannot be controlled by us. Therefore Faber Chimica Srl disclaims any liability concerning the use of such data and suggestions.*

MADE IN ITALY 100%



FABER CHIMICA SRL
60044 FABRIANO (AN) ITALY - VIA G. CERESANI 10 - LOC. CAMPO D'OLMO
PI-CF / VAT NUMBER 0100744021 - P: +39 0732 62 71 78
INFO@FABERSURFACECARE.COM - FABERSURFACECARE.COM