Litostrip

CLEANER GEL FOR THE REMOVAL OF EPOXY GROUT RESIDUE ALSO EFFECTIVE FOR THE DEEP CLEANING OF TOUGH DIRT.

DESCRIPTION

Litostrip is a clear gel made from a mix of solvents, which can easily be applied with a trowel or brush on both horizontal and vertical surfaces.

ADVANTAGES

- Ready to use
- The thick and viscous consistency makes it easy to apply even on walls
- Effective in removing consolidated epoxy residue even after some time

PACKAGING

0.8 qts. (0.75 l) metal bottles (boxes with 12 pcs)

FIELDS OF APPLICATION

Litostrip is a product designed for the total removal of Starlike® EVO or EpoxyÉlite EVO set epoxy grouts in joints, or of halos left on ceramic surfaces due to incorrect or insufficient cleaning.

APPLICATION

Shake well before use.
The product is ready to use and does not require any dilution.
Spread a thin, even layer of product on the parts to be removed using a brush or trowel.
Let the Litostrip work until the residue has softened.
10-20 minutes are normally sufficient for halos and 1 to 8 hours for the removal of set grout.
Then remove any residual epoxy grout with the aid of a metal trowel.
Wipe with a clean, dry rag to remove the gel and rinse with plenty of clean water.
If necessary, proceed with a second wash.

LIMITATIONS

- Spread the product at temperatures between 40°F and 95°F
- Do not dilute the product with water or solvents
- Before use, protect doors, windows, rubber gaskets, furniture, taps and fittings, metal or PVC profiles and all surfaces that may be damaged by direct contact with the detergents
- Change the rinse water frequently
- In the case of accidental leaks, soak up the product using an absorbent material (paper, sawdust, vermiculite, etc.) and dispose of it in a suitable container
- Handle the product with extreme care as it is easily flammable
- Do not smoke during use
- Do not use on non-solvent-resistant products such as: plastics, PVC, linoleum, decorative enamels, etc.
- In the case of polished or honed tiles and polished natural stones, perform a spot test first to check that the product doesn't dull the surface
- Do not use the product for applications not stated in this technical sheet
- If in doubt, contact the Litokol S.p.A Technical Help Service.

SAFETY INFORMATION

Consult the product safety data sheet, available on request.
PRODUCT FOR PROFESSIONAL USE

IDENTIFICATION DATA

Appearance	Clear gel
Color	Colorless
Odor	Feature
Customs code	38140090
Shelf life	24 months in original packaging away from sources of heat and direct sunlight.

APPLICATION DATA

Treatment time	10 - 20 minutes up to 8 hours
Flammable	YES
Application	Smooth steel trowel or brush
Acceptable application temperatures	From +41°F to +104°F (+5°C to +35°C)
Coverage	3 - 10 m^2/l (3.28 - 10.9yd^2/US gal lqd)

NOTES

Test performed at temperature +73.4°F (+23 °C), R.H. 50% and with no wind. May vary depending on the specific conditions of the installation site.

Form **n. 313**
Revision **n. 4**
Date: **January 2021**

The information and provisions contained in this technical data sheet reflect our best experience. Given the impossibility of directly intervening on the conditions of the work site and execution of the works, they represent indications of a general nature, which are in no way binding on our Company. It is therefore advisable to perform a spot test to check the suitability of the product for the intended use. In any case, users must determine whether or not it is suitable for the intended use and shall assume all associated responsibility.

Litokol S.p.A.
Via G. Falcone 13/1
42048 Rubiera (RE) Italy
Tel. +39 0522 622811
Fax +39 0522 620150
info@litokol.it
www.litokol.it