Starlike® Care Pro

Technical specifications

Gel pulitore per la rimozione dei residui epossidici più ostinati e stagionati da qualsiasi tipo di piastrelle, mosaici, marmi e pietre naturali. Efficace per la rimozione di graffiti, vernici spray e inchiostri.

Description

Starlike® Care Pro is a liquid detergent with an alkaline pH ideal for the removal of catalysed epoxy residue, even a long time after grouting, from all types of ceramic and porcelain tiles, including delicate surfaces such as honed ceramics, vitreous or ceramic mosaics, natural stones.
Since it has high viscosity, Starlike® Care Pro is suitable for cleaning operations on floors and walls, both indoors and outdoors.

Performance

Versatile and usable on all surfaces.
Water-based product.
Non-aggressive solution, which can also be used on polished marble and honed or polished stoneware without the risk of corrosion or tarnishing.
Effective also on stains catalysed for some time.
Excellent degreasing and wax removal power.
Thanks to its dense and viscous Gel formula, it is easily applicable even on vertical surfaces.

Uses

Used undiluted, thanks to its strong disintegrating power, the detergent is particularly effective for the removal of aged residues and stains from epoxy grouts such as Starlike® Pro, Starlike® Crystal or Starlike® Easy, as well as for the removal of stains on polished porcelain stoneware, stained by

previous grouting with dark-coloured cementitious sealants.
Also ideal for the removal of graffiti, spray paints and ink.
Effective in removing silicone residue and stains produced by organic polymers.

Product specifications

Appearance	Starlike® Care Pro - Thick Gel Liquid
Colour	Bianco
Odour	Feature
Customs code	3402909000
Responsible packaging	0.5 litre recycled plastic bottles
Shelf life	24 months in original packaging away from sources of heat and direct sunlight. Protect against frost.

Specifications for application

Treatment time	10 - 30 minutes
Flammable	No
pH	11,5 - 12,5
Specific gravity	1.12 kg/l
Application	Starlike® sponge or white felt
Application temperatures	From +5°C to +35°C
Consumption	4 - 6 m^2/l

Application

Shake well before use.
For the removal of epoxy grout halos or residue, the detergent must be applied once the grouting has totally hardened (normally after 5 days at a temperature of +20/+25°C).
For fresh residue the product requires less time to work, while for more consolidated residue, the product will need to be left in contact for longer.
Apply the pure, undiluted product, by pouring it directly onto the affected surface and spreading it evenly using a special white Starlike® pad or felt. Leave it on for about 10 - 30 min depending on the marks present.
It is recommended to mechanically rub the product when applied to facilitate its removal.
Collect the cleaning solution with a damp sponge.
Finally, rinse well with clean water and dry with a clean rag or cloth.
Do not wait for the rinse water to evaporate as this may cause stains to reappear on the surface.
If epoxy grout residue can still be seen after rinsing, repeat the application following the same procedure.

Warnings

Apply the product at temperatures between +5°C and +35°C
Wear protective clothing during handling. Follow the instructions shown on the label and safety sheet
Before use, protect doors, windows, rubber gaskets, furniture, taps and fittings, metal or PVC profiles and all surfaces that may be damaged by direct contact with the detergents
Change the rinse water frequently
In the case of accidental leaks, soak up the product using an absorbent material (paper, sawdust, vermiculite, etc.) and dispose of it in a suitable container

Do not use the product for applications not indicated in this technical data sheet
For further information, contact the Litokol Technical Help Service at +39-0522-622811 or via customercare@litokol.com

Information regarding safety

For the safe use of our products, refer to the latest version of the Safety Data Sheet, available on the website www.litokol.com
PRODUCT FOR PROFESSIONAL USE

Legal notes

The information and provisions contained in this technical data sheet reflect our best experience.
Given the impossibility of directly intervening on the conditions of the work site and execution of the works, they represent indications of a general nature, which are in no way binding for our Company.
It is therefore recommended to perform a spot test in order to check the suitability of the product for the intended use. In any case, those who intend to use the product must establish whether or not it is suitable for the intended use, and in any case assume all liability for any consequences resulting from such use.
Always refer to the latest updated version of the technical data sheet, available on the website www.litokol.com

Data sheet **n. 411**
Revision **n. 0**
Date: **05 25**

Litokol

Litokol Lab Spa Via G. Falcone 13/1 42048 Rubiera RE Italy
Tel. +39 0522 622811 info@litokol.com www.litokol.com