PROFESSIONAL LINE

Protective Treatments

HIDRO 150

High-performing, water-based stain-resistant treatment for natural stone, terracotta, and agglomerates.

HIDRO 150 is a water-based stain-resistant treatment with a natural finish. **HIDRO 150** it's quick and easy to apply; it doesn't create a surface film and therefore it does not change the original breathability of the treated surface. **HIDRO 150** is certified safe for food contact surfaces making it ideal for the protection of countertops and table tops.

BENEFITS

- ✓ Certified safe for food contact
- ✓ High stain-resistant properties
- ✓ It doesn't change the color of the material
- ✓ It won't yellow overtime

USES

This product can be used on both indoor and outdoor surfaces.
Suitable for use on: Marble, Sandstone, Granite, Limestone, Slate, Basaltina, Quarzite, Porphyry, Travertine, Terracotta, Marble-concrete agglomerate, Marble-resin agglomerate, Quartz-resin agglomerate

COVERAGE

32 fl oz can cover 107-161 ft²

APPLICATION EQUIPMENT

Brush, Lambswool applicator, Roller, Cloth

APPLICATION STEPS

Surface preparation

- Carefully clean the surface, making sure to remove any dust or dirt present.
- Never apply **HIDRO 150** to wet or damp surfaces.
- Apply **HIDRO 150** to surfaces with a temperature between +40 and +100°F
- Any surfaces in direct proximity not being treated must be protected.

Application

Before applying the product is necessary to take a preliminary test on an unexposed area or unused piece of material to check the product's suitability.

- Apply an even, thin coat of product to a clean, dry surface with the preferred tool, making sure to create an even layer to cover the whole surface being treated
- The product is fast drying and usually does not create residues. When applied to a compact surface that is not very absorbent, it could leave slight residues on the surface that can be easily wiped off with a clean, dry cloth. In case of very absorbent surfaces, we recommend applying a second coat of product, no less than 45 minutes after the first.

Drying Time

The product dries quickly, within an hour from the application.

Resume Surface Use

Resume the use of the surface after 2-3 hours from the application

MADE IN ITALY

100%

FABER CHIMICA SRL
60044 FABRIANO (AN) ITALY - VIA G. CERESANI 10 - LOC. CAMPO D'OLMO
PI-CF / VAT NUMBER 0100744021 - P: +39 0732 62 71 78
INFO@FABERSURFACECARE.COM - FABERSURFACECARE.COM

MAINTENANCE PRODUCTS

- For the daily cleaning of a surface treated with **HIDRO 150**, we recommend: **NEUGEL** or **ALGAFLOOR**
- For heavy-duty cleaning of a surface treated with **HIDRO 150**, we recommend: **FABER 30** or **DETERFUG** according to the type of material

INSTRUCTIONS AND GUIDELINES

- Never apply the product to wet or damp surfaces.
- If the product is applied as a stain-proof treatment on a material that has already been primed with a high penetrating water-repellent sealer, wait for this to dry completely before applying **HIDRO 150.**
- Do not apply the product to overly heated surfaces.
- Do not apply the product when there is an imminent risk of rain or frost, or in the presence of mist, fog, or high levels of humidity.
- Apply the product to surfaces with a temperature of between +40 and +100°F
- When applying to recently laid or grouted surfaces, wait for the adhesive or grout to cure completely.
- Before applying the product to the whole surface, it is advisable to test a small, unexposed area or unused piece to check its suitability for use.

EQUIPMENT CLEANING

At the end of the application, the equipment used can be washed using water.

PHYSICAL-TECHNICAL DATA

Formula	Liquid
Color	Amber
Odor	Light scent
Specific gravity a 20°C	1010 ± 10 g/l
pH	11 ± 0,4

STORAGE

Keep the container tightly closed and store in a cool, dry place.

SHELF LIFE

24 months in the original, sealed packaging, stored in a cool, dry place.

PACKAGING

32 fl oz bottles – 12 bottles per box
169 fl oz bottles – 4 bottles per box

SAFETY

When applying the product, always use suitable personal protective equipment and follow the product safety data sheet instructions with care.

Revisione 5.1 – 17/02/2025

This technical data sheet supersedes all previous versions. Always refer to the latest version of the data sheet, available on www.fabersurfacecare.com site. Faber Chimica reserves the right to update and/or modify the data and information contained in the datasheet.

The information in this data sheet is based on our wide experience in technical and operational research. In any case, you should always make a preliminary test to verify the suitability of the product for the intended use and the type of material on which it will be applied. The information and the suggestions can't be construed as a commitment or result in our responsibility as the conditions and method of use of the product cannot be controlled by us. Therefore Faber Chimica Srl disclaims any liability concerning the use of such data and suggestions.

FABER CHIMICA SRL
60044 FABRIANO (AN) ITALY - VIA G. CERESANI 10 - LOC. CAMPO D'OLMO
PI-CF / VAT NUMBER 0100744021 - P: +39 0732 62 71 78
INFO@FABERSURFACECARE.COM - FABERSURFACECARE.COM

MADE IN ITALY
100%