PROFESSIONAL LINE

*Protective Treatments*

# PROTW LUX

## Fast-drying, Solvent-based, Stain-resistant Treatment for Marble, Granite, Natural Stone

**PROTW LUX** is a fast-drying, solvent-based, stain-resistant treatment. The product does not change the color of the material maintaining its natural look. The product provides long-lasting stain-resistant features to the material it applies. Certified safe for use on surfaces in contact with food, makes it the ideal solution for kitchen countertops.

**BENEFITS**

- ✓ Great stain-resistant properties
- ✓ UV resistant
- ✓ It preserves the natural look of the surface
- ✓ It won't yellow overtime

**USES**

**Suitable for** indoor and outdoor applications.
**Suitable for** Marble, Sandstone, Limestone, Granite, Slate, Basaltina, Quartzite, Porphyry, Travertine, Cotto, Terracotta, Marble-resin agglomerate, Marble-cement agglomerate, Quartz-resin agglomerate

**COVERAGE**

32 fl oz can cover 107-160 ft²

**APPLICATION EQUIPMENT**

Brush, Lambswool applicator, Roller, Cloth

**APPLICATION STEPS**

### *Surface preparation*

- Carefully clean the surface, making sure to remove any dust or dirt present.
- Never apply **PROTW LUX** to wet or damp surfaces.
- Apply **PROTW LUX** to surfaces with a temperature between +40 and +100°F
- Any surfaces in direct proximity not being treated must be protected.

### *Application*

*Before applying the product is necessary to take a preliminary test on an unexposed area or unused piece of material to check the product's suitability.*

- On a clean and dry surface apply a thin and even layer of product using the preferred tool making sure to cover the whole surface.
- The product dries quickly, residues can be easily removed using a dry clean cloth.
- In case of high absorbing materials we recommend applying a second coat of product. Make sure to wait at least 45 minutes in between applications.

### *Drying Time*

The product dries quickly, within 45 minutes of the application.

### *Resume Surface Use*

Resume the use of the surface after 2-3 hours from the application

MADE IN ITALY 100%



FABER CHIMICA SRL
60044 FABRIANO (AN) ITALY - VIA G. CERESANI 10 - LOC. CAMPO D'OLMO
PI-CF / VAT NUMBER 0100744021 - P: +39 0732 62 71 78
INFO@FABERSURFACECARE.COM - FABERSURFACECARE.COM

**MAINTENANCE PRODUCTS**

- For the daily cleaning of a surface treated with **PROTW LUX**, we recommend: **NEUGEL** or **ALGAFLOOR**
- For heavy-duty cleaning of a surface treated with **PROTW LUX**, we recommend: **FABER 30 2.0** or **DETERFUG** according to the type of material
- To remove **PROTW LUX** we recommend: **DEC 21** and/or **DECERA/P** depending on the material .

**INSTRUCTIONS AND GUIDELINES**

- Never apply the product to wet or damp surfaces.
- If the product is applied as a stain-proof treatment on a material that has already been primed with a high penetrating water-repellent sealer, wait for this to dry completely before applying **PROTW LUX.**
- Do not apply the product to overly heated surfaces.
- Do not apply the product when there is an imminent risk of rain or frost or in the presence of mist, fog, or high levels of humidity.
- Apply the product to surfaces with a temperature of between +40 and +100°F
- When applying to recently laid or grouted surfaces, wait for the adhesive or grout to cure completely.
- Before applying the product to the whole surface, it is advisable to test a small, unexposed area or unused piece to check its suitability for use.

**EQUIPMENT CLEANING**

At the end of the application, the equipment used can be washed using white spirit.

**PHYSICAL-TECHNICAL DATA**

| | |
|---|---|
| Formula | liquid |
| Color | clear |
| Odor | solvent |
| Specific gravity a 20°C | >27°C |
| Flash Point (ASTM D 56) | 0.890 kg/l |

**STORAGE**

Keep the container tightly closed and store in a cool, dry place.

**SHELF LIFE**

36 months in the original, sealed packaging, stored in a cool, dry place.

**PACKAGING**

32 fl oz bottles – 12 bottles per box
169 fl oz bottles – 4 bottles per box

**SAFETY**

When applying the product, always use suitable personal protective equipment and follow the product safety data sheet instructions with care.

**Revisione 3.1 – 17/02/2025**

**This technical data sheet supersedes all previous versions. Always refer to the latest version of the data sheet, available on www.fabersurfacecare.com site. Faber Chimica reserves the right to update and/or modify the data and information contained in the datasheet.**

*The information in this data sheet is based on our wide experience in technical and operational research. In any case, you should always make a preliminary test to verify the suitability of the product for the intended use and the type of material on which it will be applied. The information and the suggestions can't be construed as a commitment or result in our responsibility as the conditions and method of use of the product cannot be controlled by us. Therefore Faber Chimica Srl disclaims any liability concerning the use of such data and suggestions.*



FABER CHIMICA SRL
60044 FABRIANO (AN) ITALY - VIA G. CERESANI 10 - LOC. CAMPO D'OLMO
PI-CF / VAT NUMBER 0100744021 - P: +39 0732 62 71 78
INFO@FABERSURFACECARE.COM - FABERSURFACECARE.COM

MADE IN ITALY
100%