PROFESSIONAL LINE

Cleaners

SCRATCH OFF CLEANER

Concentrated alkaline cleaner for the preliminary cleaning of porcelain slabs before the restoration with SCRATCH OFF DARK and SCARCTH OFF LIGHT

SCRATCH OFF CLEANER is a concentrated alkaline-based cleaner that is extremely effective for the preliminary cleaning before the porcelain slab restoration using **SCRATCH OFF DARK** or **SCRATCH OFF LIGHT**.
SCRATCH OFF CLEANER is one of three products that constitute our **SCRATCH OFF KIT.**

BENEFITS

- ✓ Extremely effective on different types of dirt
- ✓ Deep extractive action
- ✓ Alkaline formula

USES

This product can be used on both indoor and outdoor surfaces.
Suitable for use on Porcelain and ceramic slabs and tiles.

COVERAGE

10/15 m^2/l

APPLICATION EQUIPMENT

White pad

APPLICATION STEPS

Surface Preparation

Before proceeding with the cleaning, it is advisable to remove any surface residues, such as dust, debris, and coarse dirt, using a broom or a vacuum cleaner

Application before the installation

Before applying the product is necessary to take a preliminary test on an unexposed area or unused piece of material to check the product's suitability.

The product can be used undiluted or it can be diluted in clean water, according to the amount of dirt that needs to be removed:

- If used to remove stubborn dirt the product should be diluted to 20-30% in water (1 part of product in 2/4 parts of water)
- If used as simple cleaning products to clean a ceramic slab before the restoration the product should be diluted to 10% in water (1 part of product in 9 parts of water)

Apply the product in the selected dilution ratio to the surface, covering the whole area being cleaned and distributing it evenly and vigorously with a white pad.

Let it work for about 10-15 minutes, buffing it on the surface every now and than. This will boost the dissolving action of the product and give you better results.

Remove the residues and rinse well with clean water. If the result is not satisfactory, repeat the application, following the steps above.

MADE IN ITALY
100%

FABER CHIMICA SRL
60044 FABRIANO (AN) ITALY - VIA G. CERESANI 10 - LOC. CAMPO D'OLMO
PI-CF / VAT NUMBER 0100744021 - P: +39 0732 62 71 78
INFO@FABERSURFACECARE.COM - FABERSURFACECARE.COM

INSTRUCTIONS AND GUIDELINES

- Don’t apply the product on an overheated surface
- When applying to recently laid or grouted surfaces, wait for the adhesive or grout to cure completely.
- Don’t mix with other chemicals unless specified
- All surfaces close by not to be treated must be protected
- Before applying the product to the whole surface, it is advisable to test a small, unexposed area or unused piece to check its suitability for use.

EQUIPMENT CLEANING

At the end of application, the equipment used can be washed using water.

PHYSICAL-TECHNICAL DATA

Formula	Liquid
Color	Amber
Odor	Typical
pH:	13 ± 0,5
Specific Gravity at 20°C	1054 ± 10 g/l

STORAGE

Keep the container tightly closed and store in a cool, dry place.

SHELF LIFE

36 months in the original, sealed packaging, stored in a cool, dry place.

PACKAGING

500 ml bottles

SAFETY

When applying the product, always use suitable personal protective equipment and follow the product safety data sheet instructions with care.

Rev. 2.0 – 17/06/2024

This technical data sheet supersedes all previous versions. Always refer to the latest version of the data sheet, available on www.fabersurfacecare.com site. Faber Chimica reserves the right to update and/or modify the data and information contained in the datasheet.

The information in this data sheet is based on our wide experience in technical and operational research. In any case, you should always make a preliminary test to verify the suitability of the product for the intended use and the type of material on which it will be applied. The information and the suggestions can't be construed as a commitment or result in our responsibility as the product's conditions and method of use cannot be controlled by us. Therefore Faber Chimica Srl disclaims any liability concerning the use of such data and suggestions.

FABER CHIMICA SRL
60044 FABRIANO (AN) ITALY - VIA G. CERESANI 10 - LOC. CAMPO D'OLMO
PI-CF / VAT NUMBER 0100744021 - P: +39 0732 62 71 78
INFO@FABERSURFACECARE.COM - FABERSURFACECARE.COM

MADE IN ITALY
100%

PROFESSIONAL LINE

Honing & Polishing

SCRATCH OFF DARK

Professional treatment for the restoration of scratches, abrasions, dullness and defects from dark-colored polished porcelain ceramic tiles and slabs

SCRATCH OFF DARK is an innovative water-based product specifically developed to restore scratches, defects, abrasions, and dullness from dark-colored glazed polished porcelain tiles.

BENEFITS

- ✓ It can be used before or after setting
- ✓ Suitable to restore scratches and dullness
- ✓ It doesn't require water for the application

USES

This product can be used on both indoor and outdoor surfaces.
This product is suitable for use on dark-colored glazed polished porcelain tiles and slabs

APPLICATION EQUIPMENT

Hand-polisher with customizable rpm equipped with the FAB K pads provided with the **SCRATCH OFF KIT**.
During the application the tool should be set at 700-1500 rpms.

APPLICATION STEPS

Surface preparation

- Carefully clean the surface removing dust and dirt to do so we recommend using **SCRATCH OFF CLEANER** (see product Technical Data Sheet)
- Rinse well the surface with water making sure is completely dry afterwards
- Before apply the product we suggest to delimiting the area to be treated with masking tape and plastic film

Application

Before applying the product is necessary to take a preliminary test on an unexposed area or unused piece of material to check the product's suitability.

- Shake the bottle and apply a few drops over the area that needs to be restored.
- Without turning on the polisher, distribute the product on the surface using the **FAB K Pad**
- Turn on the polisher and star buffing the product going very slowly on the surface with linear movements that follows the direction of the scratch. Do not apply too much pression on the tool. Make sure that during the application the tool and the pad are flat over the scratched area.
- Keep buffing untill the product is completely dry. If you notice some product buildup on the sides, those will be easily removed once the application is over.
- When the product is completly dry on the surface evaluate the achieved result. If the scratch is still visible, repeat the application by following the same instructions. The number of applications necessary to have a full restoration depends from the depth and wide of the scratch. Generally, as an indication, 3-5 applications are enough to have a satisfactory result, however for deeper or wider scratches is possible to make all the application necessary for a full restoration.
- Make sure to evaluate how hot the surface gets after each application. If the surface overheats to the point where you can no longer keep your hand on it

MADE IN ITALY
100%

FABER CHIMICA SRL
60044 FABRIANO (AN) ITALY - VIA G. CERESANI 10 - LOC. CAMPO D'OLMO
PI-CF / VAT NUMBER 0100744021 - P: +39 0732 62 71 78
INFO@FABERSURFACECARE.COM - FABERSURFACECARE.COM

we recommend you to stop and wait until it gets cooler again.

APPLICATION STEPS

- Once the desired result is achieved rinse well with clean water and the WHITE PAD provided in the kit. At the end wipe the surface with a paper towel or a cloth.
  To remove any stubborn residues we recommend using **SHINE REPAIR DARK.**

Resuming the surface use

After carefully removing all residues and rinsing the surface with water resume the use of the surface.

INSTRUCTIONS AND GUIDELINES

- Shake very well the bottle before use
- Proceed with the application one scratch at time
- Do not work on large areas
- Do not apply too much pression on the hand-tool
- Do not apply on wet surface
- Do not apply on over-heated surface
- Do not apply on light-colored surfaces
- Before apply the product on the whole surface, always make a preliminary test to evaluate the final result.

EQUIPMENT CLEANING

At the end of application, the equipment used can be washed using water.

PHYSICAL-TECHNICAL DATA

Formula	Liquid
Color	Black
Odor	Unscented
pH:	10 ± 0,4
Specific Gravity at 20°C	1320 ± 10 g/l

STORAGE

Keep the container tightly closed and store in a cool, dry place.

SHELF LIFE

36 months in the original, sealed packaging, stored in a cool, dry place.

PACKAGING

250 ml Bottle – 12 bottles per box

SAFETY

When applying the product, always use suitable personal protective equipment and follow the product safety data sheet instructions with care.

Revisione 1.0 – 05/06/2024

This technical data sheet supersedes all previous versions. Always refer to the latest version of the data sheet, available on www.fabersurfacecare.com site. Faber Chimica reserves the right to update and/or modify the data and information contained in the datasheet.

The information in this data sheet is based on our wide experience in technical and operational research. In any case, you should always make a preliminary test to verify the suitability of the product for the intended use and the type of material on which it will be applied. The information and the suggestions can't be construed as a commitment or result in our responsibility as the conditions and method of use of the product cannot be controlled by us. Therefore Faber Chimica Srl disclaims any liability concerning the use of such data and suggestions.

FABER CHIMICA SRL
60044 FABRIANO (AN) ITALY - VIA G. CERESANI 10 - LOC. CAMPO D'OLMO
PI-CF / VAT NUMBER 0100744021 - P: +39 0732 62 71 78
INFO@FABERSURFACECARE.COM - FABERSURFACECARE.COM

MADE IN ITALY
100%

PROFESSIONAL LINE

Honing & Polishing

SCRATCH OFF LIGHT

Professional treatment for the restoration of scratches, abrasions, dullness and defects from polished porcelain ceramic tiles and slabs

SCRATCH OFF LIGHT is an innovative water-based product specifically developed to restore scratches, defects, abrasions, and dullness from glazed polished porcelain tiles.

BENEFITS

- ✓ It can be used before or after setting
- ✓ Suitable to restore scratches and dullness
- ✓ It doesn't require water for the application

USES

This product can be used on both indoor and outdoor surfaces.
This product is suitable for use on glazed polished porcelain tiles and slabs

APPLICATION EQUIPMENT

Hand-polisher with customizable rpm equipped with the FAB K pads provided with the **SCRATCH OFF KIT**.
During the application the tool should be set at 700-1500 rpms.

APPLICATION STEPS

Surface preparation

- Carefully clean the surface removing dust and dirt to do so we recommend using **SCRATCH OFF CLEANER** (see product Technical Data Sheet)
- Rinse well the surface with water making sure is completely dry afterwards
- Before apply the product we suggest to delimiting the area to be treated with masking tape and plastic film

Application

Before applying the product is necessary to take a preliminary test on an unexposed area or unused piece of material to check the product's suitability.

- Shake the bottle and apply a few drops over the area that needs to be restored.
- Without turning on the polisher, distribute the product on the surface using the **FAB K Pad**
- Turn on the polisher and star buffing the product going very slowly on the surface with linear movements that follows the direction of the scratch. Do not apply too much pression on the tool. Make sure that during the application the tool and the pad are flat over the scratched area.
- Keep buffing untill the product is completely dry. If you notice some product buildup on the sides, those will be easily removed once the application is over.
- When the product is completly dry on the surface evaluate the achieved result. If the scratch is still visible, repeat the application by following the same instructions. The number of applications necessary to have a full restoration depends from the depth and wide of the scratch. Generally, as an indication, 3-5 applications are enough to have a satisfactory result, however for deeper or wider scratches is possible to make all the application necessary for a full restoration.
- Make sure to evaluate how hot the surface gets after each application. If the surface overheats to the point where you can no longer keep your hand on it we recommend you to stop and wait until it gets cooler again.

MADE IN ITALY
100%

FABER CHIMICA SRL
60044 FABRIANO (AN) ITALY - VIA G. CERESANI 10 - LOC. CAMPO D'OLMO
PI-CF / VAT NUMBER 0100744021 - P: +39 0732 62 71 78
INFO@FABERSURFACECARE.COM - FABERSURFACECARE.COM

PROFESSIONAL LINE

APPLICATION STEPS

- Once the desired result is achieved rinse well with clean water and the WHITE PAD provided in the kit. At the end wipe the surface with a paper towel or a cloth.
  To remove any stubborn residues we recommend using **SHINE REPAIR LIGHT.**

Resuming the surface use

After carefully removing all residues and rinsing the surface with water resume the use of the surface.

INSTRUCTIONS AND GUIDELINES

- Shake very well the bottle before use
- Proceed with the application one scratch at time
- Do not work on large areas
- Do not apply too much pression on the hand-tool
- Do not apply on wet surface
- Do not apply on over-heated surface
- Before apply the product on the whole surface, always make a preliminary test to evaluate the final result.

EQUIPMENT CLEANING

At the end of application, the equipment used can be washed using water.

PHYSICAL-TECHNICAL DATA

Formula	Liquid
Color	White
Odor	Unscented
pH:	10 ± 0,6
Specific Gravity at 20°C	1316 ± 10 g/l

STORAGE

Keep the container tightly closed and store in a cool, dry place.

SHELF LIFE

36 months in the original, sealed packaging, stored in a cool, dry place.

PACKAGING

250 ml Bottle – 12 bottles per box

SAFETY

When applying the product, always use suitable personal protective equipment and follow the product safety data sheet instructions with care.

Revisione 1.0 – 05/06/2024

This technical data sheet supersedes all previous versions. Always refer to the latest version of the data sheet, available on www.fabersurfacecare.com site. Faber Chimica reserves the right to update and/or modify the data and information contained in the datasheet.

The information in this data sheet is based on our wide experience in technical and operational research. In any case, you should always make a preliminary test to verify the suitability of the product for the intended use and the type of material on which it will be applied. The information and the suggestions can't be construed as a commitment or result in our responsibility as the conditions and method of use of the product cannot be controlled by us. Therefore Faber Chimica Srl disclaims any liability concerning the use of such data and suggestions.

MADE IN ITALY

100%

FABER CHIMICA SRL
60044 FABRIANO (AN) ITALY - VIA G. CERESANI 10 - LOC. CAMPO D'OLMO
PI-CF / VAT NUMBER 0100744021 - P: +39 0732 62 71 78
INFO@FABERSURFACECARE.COM - FABERSURFACECARE.COM