PROFESSIONAL LINE

Protective Treatments

WET LOOK ECO

Water-based, color-enhancing, stain-resistant treatment for absorbing materials

WET LOOK ECO is a water-based, stain-resistant, color enhancing treatment. It is used to intensify the color of absorbent surfaces, providing a satin or matt finish depending on the surface. **WET LOOK ECO** is suitable for materials with a medium-high degree of absorption.

BENEFITS

- ✓ Color enhancing features
- ✓ It penetrates the material
- ✓ Stain resistant properties
- ✓ It won't yellow overtime

USES

Product suitable for application indoor and outdoor on natural stone, Terracotta, Bricks, Concrete, Agglomerates and Concrete Tiles

COVERAGE

32 fl oz can cover 107-160 ft²

APPLICATION EQUIPMENT

Brush, Lambswool applicator, Roller

APPLICATION STEPS

Surface preparation

- Carefully clean the surface, making sure to remove any dust or dirt present.
- Never apply **WET LOOK ECO** to wet or damp surfaces.
- Apply **WET LOOK ECO** to surfaces with a temperature between +40 and +100°F
- Any surfaces in direct proximity not being treated must be protected.

Application

Before applying the product is necessary to take a preliminary test on an unexposed area or unused piece of material to check the product's suitability.

Depending on the degree of absoption of the material the product can be used:

- Undiluted, in case of high absorbing materials and rough finishes
- Diluted 1:1 in water for medium to medium-high absorbing materials and textured finishes
- Diluted 1:2 in water in case of medium absorbing surfaces and compact surfaces

On a clean and dry surface apply a thin and even layer of product using the preferred tool making sure to evenly cover the whole surface.

When applied on high absorbing materials the product will be absorbed by the surface during or immediately after its application.

When applied on surfaces with a lower absorbing ability the product can create a superficial residue. The residue must be removed after its application before the product dries. Alternatively the residue can be buffed to create a satin finish.

MADE IN ITALY 100%

FABER CHIMICA SRL
60044 FABRIANO (AN) ITALY - VIA G. CERESANI 10 - LOC. CAMPO D'OLMO
PI-CF / VAT NUMBER 0100744021 - P: +39 0732 62 71 78
INFO@FABERSURFACECARE.COM - FABERSURFACECARE.COM

PROFESSIONAL LINE

APPLICATION STEPS

When applied to high absorbing surfaces, if a second coat of product should be necessary we recommend to wait at least 2-3 hours from the first application.

When applied to more compact surfaces we recommend waiting 5 minutes max before removing or buffing the residue.
When the product residues are buffed it will provide a satin finish.

To remove the residue and avoid enhancing the shine of the surface it is necessary to remove the residues using the same tool used during the application without adding more product on the surface. Doing so will minimize the residues facilitating the drying process.

To buff the product enhancing the shine of the surface it is necessary the once the residues have been evenly distributed to buff the product using a single disk machine or a hand polisher. We recommend buffing it a first time using a clean white pad and immediately after buff it again using a felt pad this time.
Keep buffing until the surface is dry to the touch.

Drying Time

The product dries quickly, within 1-2 hours of the application.

Resume Surface Use

Resume the use of the surface after 4-6 hours from the application

MAINTENANCE PRODUCTS

- For the daily cleaning of a surface treated with **WET LOOK ECO**, we recommend: **NEUGEL** or **ALGAFLOOR**
- For heavy-duty cleaning of a surface treated with **WET LOOK ECO**, we recommend: **FABER 30 2.0** or **DETERFUG** according to the type of material
- To remove **WET LOOK ECO** we recommend: **DEC 21** and/or **DECERA/P** depending on the material .

INSTRUCTIONS AND GUIDELINES

- Never apply the product to wet or damp surfaces.
- If the product is applied as a stain-proof treatment on a material that has already been primed with a high penetrating water-repellent sealer, wait for this to dry completely before applying **WET LOOK ECO.**
- Do not apply the product to overly heated surfaces.
- Do not apply the product when there is an imminent risk of rain or frost or in the presence of mist, fog, or high levels of humidity.
- Apply the product to surfaces with a temperature of between +40 and +100°F
- When applying to recently laid or grouted surfaces, wait for the adhesive or grout to cure completely.
- Before applying the product to the whole surface, it is advisable to test a small, unexposed area or unused piece to check its suitability for use.
- Not suitable for porcelain tiles and quartz.

EQUIPMENT CLEANING

At the end of the application, the equipment used can be washed using water.

MADE IN ITALY

100%

FABER CHIMICA SRL
60044 FABRIANO (AN) ITALY - VIA G. CERESANI 10 - LOC. CAMPO D'OLMO
PI-CF / VAT NUMBER 0100744021 - P: +39 0732 62 71 78
INFO@FABERSURFACECARE.COM - FABERSURFACECARE.COM

PHYSICAL-TECHNICAL DATA

Formula	Liquid
Color	White
Odor	Unscented
Specific gravity a 20°C	991 ± 10 g/l

STORAGE Keep the container tightly closed and store in a cool, dry place.

SHELF LIFE 24 months in the original, sealed packaging, stored in a cool, dry place.

PACKAGING 32 fl oz bottles – 12 bottles per box
169 fl oz bottles – 4 bottles per box

SAFETY When applying the product, always use suitable personal protective equipment and follow the product safety data sheet instructions with care.

Revisione 2.0 – 17/02/2025

This technical data sheet supersedes all previous versions. Always refer to the latest version of the data sheet, available on www.fabersurfacecare.com site. Faber Chimica reserves the right to update and/or modify the data and information contained in the datasheet.

The information in this data sheet is based on our wide experience in technical and operational research. In any case, you should always make a preliminary test to verify the suitability of the product for the intended use and the type of material on which it will be applied. The information and the suggestions can't be construed as a commitment or result in our responsibility as the conditions and method of use of the product cannot be controlled by us. Therefore Faber Chimica Srl disclaims any liability concerning the use of such data and suggestions.

MADE IN ITALY
100%

FABER CHIMICA SRL
60044 FABRIANO (AN) ITALY - VIA G. CERESANI 10 - LOC. CAMPO D'OLMO
PI-CF / VAT NUMBER 0100744021 - P: +39 0732 62 71 78
INFO@FABERSURFACECARE.COM - FABERSURFACECARE.COM